

ACA-Steel-slim

Touchless steel slim Exit button

Product Overview

The touchless exit buttons provide means to activate a request-to-exit with access control solutions without having to touch anything. This solution is achieved by using Infrared technology. Just move a hand near the front of the sensor to activate the contact. Activation is clearly indicated by an LED showing Green when active or Blue when powered but not active.

Please note that direct sunlight or reflections may affect the sensitivity of the infrared sensor.



Details

- Touchless exit button using IR sensor
- Attractive, timeless stainless steel design
- Adjustable distance, 3-15 cm
- Adjustable relay activation period
- Blue and Green LED indication for standby and active
- Indoor use only

ACA-Steel-slim

Touchless steel slim Exit button

Technical specifications

General

| | |
|-----------------|----------------|
| Accessory group | Access control |
| Type | Exit device |

Electrical

| | |
|---------------------|----------------------------|
| Operating voltage | 12- 24VDC |
| Current consumption | 30 mA Idle 35 mA Active |

Physical

| | |
|---------------------|------------------|
| Physical dimensions | 115 x 40 x 30 mm |
| Material | Stainless steel |

Environmental

| | |
|-----------------------|-------------------|
| Operating temperature | -10 to +55°C |
| Relative humidity | 95% noncondensing |
| Environment | Indoor |

Standards & regulation

| | |
|---------------|----|
| Compliance | CE |
| Certification | CE |



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 21 October 2021 - 16:23