

# ACA-Touch

#### **Product Overview**

The touchless exit buttons provide means to activate a request-to-exit with access control solutions without having to touch anything. This solution is achieved by using Infrared technology. Just move a hand near the front of the sensor to activate the contact. Activation is clearly indicated by an LED showing Green when active or RED when powered but not active.

Please note that direct sunlight or reflections may affect the sensitivity of the infrared sensor.



#### **Details**

- Touchless exit button using IR sensor
- Attractive, timeless design
- Adjustable distance, 3-15 cm
- Adjustable relay activation period
- Red and Green LED indication for standby and active
- Indoor use only

## ACA-Touch

### **Technical specifications**

Certification

General	
Accessory group	Access control
Туре	Exit device
Electrical	
Operating voltage	12- 24VDC
Current consumption	30 mA Idle
	35 mA Active
Physical	
Physical dimensions	86 x 86 x 20 mm
Colour	White
Material	ABS
Environmental	
Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing
Environment	Indoor
Standards & regulation	
Compliancy	CE

CE



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.