

## UNIVERSAL LOCK RELEASE N-512-S CTC



**Reference:** 29670

**Flush mounted Door lock.**

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is...

### DESCRIPTION

**Flush mounted Door lock.**

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanism and a shield if it is flush mounted.

**CTC**

This electric lock consists of a UNIVERSAL electrical mechanism with CTC, dimensions:

113(V)x20(H)mm

This version admits several applications thanks to its highly reliable C/No/Nc gold contact microswitch. Maximum contact intensity is 2A-230Vac. Shows whether the door is open or closed. Indispensable in security and alarm installations in banks, laboratories, jewellery stores and all premises that call for door opening with automatic blocking of another and vice versa. See installation example on page 61 of the DOOR LOCK RELEASE CATALOGUE. This model does not accept MAX version

**Reversible (Right DIN or Left DIN).**

Allows to open the door from right and left.

**Non-symmetrical.**

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

**DIN STANDARD**

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

**Operating type.**

There are several types of door lock release mechanisms depending on the type of operation needed.

**N-512 Inverted type 12Vdc** (Inverted Operation and 12 Vdc activation)

The door release is automatically unlocked when the 12 Vdc pulse stops.

**S type flush shield.**

For access doors.

S type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release.

**Dimensions: 25(H)x160(V) mm.**

### TECHNICAL SPECIFICATIONS

Consumption:



N, A 12Vac: 980mA  
N-412 12Vdc: 150mA.  
N-512 12Vdc: 150mA.  
N-424 24Vdc: 120mA.  
N-524 24Vdc: 120mA.

**Weight:** 0,2965 kg

**Size of product when packed:** 3,4x16,3x2,7 cm

**EAN 13:** 8424299296708

---