

VDS PROGRAMMER

**Reference:** 03265

The VDS installation checker is a device designed for technical services and installers that enables them to check the state of a VDS installation by means of the following functions:

- L : Automatic...

DESCRIPTION

The VDS installation checker is a device designed for technical services and installers that enables them to check the state of a VDS installation by means of the following functions:

- L : Automatic installation checker. Indicates whether the line is in standby mode or in conversation. Shows the voltage between negative and " L" in any case.
- SPY : Spy. Shows the data traffic from the installation it is connected to.
- PnL : Auxiliary Panel. Lets you program the installation telephones/monitors and make calls as if from an outdoor panel.
- Non : Checks the presence of the main panel in the installation.

May be connected directly to any point of the installation bus or the test connector of the outdoor panel's VDS amplifier.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring. The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "Door open, please close after entering".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

TECHNICAL SPECIFICATIONS

Power supply: 18 Vdc



Weight: 0,1606 kg

Size of product when packed: 6,5x18x10 cm

EAN 13: 8424299032658
