

LOFT MONITOR COLOR 4+N 3,5



Reference: 03307

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

DESCRIPTION

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

A new concept in home monitors. Integrated design, in line with new trends and lifestyles, simple and functional, combining quality and design. The harmony of the gentle, relaxed shapes and the integrated volume concept are the synthesis of LOFT technology and design.

Its purity of line, technology and performance make this equipment an elegant and perfect element for any home.

Made in high impact ABS plastic, with a textured finish for easy cleaning and ultraviolet protection for greater resistance to sunlight.

Conventional System: uses wires common to the whole installation plus 1 call wire (or call return) per home..

Recommended in small to medium-sized buildings (up to 50 residents approx), with several accesses and central guard unit. For residential complexes with general entrance and interior blocks.

Wiring:

- Audio door entry system: 4 common wires + N (1 call wire per home).
- Video door entry system: 7 common wires + 1 video coaxial+N (1 call wire per home).

Maximum distance in the installation based on the cable section used (see technical manuals).

TECHNICAL SPECIFICATIONS

Screen TFT 3.5". Resolution: 480 (H) x 234 (V) lines.

Terminal has a built-in magnet in the earpiece area that ensures the arm is well fitted and fixed to the base. This prevents the arm falling off damaging the wall when hanging up and also avoids faults caused in the installation by being badly hung.



Dimensions: 220x203x60 mm (height-width-depth):

Power supply:

- Audio: 12 Vac
- Video: 18 Vdc

Door release and guard unit call button.

Auto-on button for main camera activation.

Call volume control

Colour, brightness and contrast control.

On/off control

With 2 pushbuttons for additional functions (without functions assigned).

Consumption: - in standby: 8 mA - active: 400 mA

Weight: 0,93015 kg

Size of product when packed: 27,2x23,9x6,5 cm

EAN 13: 8424299033075