

MEMOKEY CITY CLASSIC READER



Reference: 03610

Telephone type keypad that lets you open the door when a previously programmed 6 digit code is entered.

DESCRIPTION

Telephone type keypad that lets you open the door when a previously programmed 6 digit code is entered.

CityLine Classic is the "continuous profile" outdoor panel line for buildings.

The PANELS are manufactured in anodized aluminium, highly resistant to rough weather and climate changes.

The panel design stands out for its curved-convex profile. A cellular rubber airtight seal included assures a perfect panel-to-wall fit to prevent water filtrations.

Available in several colours: aluminium, golden or bronze and white.

It is possible to combine two or more panels, as long as they are from the same series. For a perfect fit, a set of separators should be used for every two panels installed between their flush mounted boxes.

Colour aluminium

Stand-alone Access Control System. For installations where a simple access control is required, with no incidents record, to complement the audio/video door entry system and enable access to the building for residents, for example: offices, small businesses, garages.

TECHNICAL SPECIFICATIONS

Series 1 Panel.

- Panel measurements: 130x128 mm (width-height):
- Flush-fit box dimensions: 115x114x45 mm (height-width-depth):
- Surface mounted box dimensions: 130x128x33 mm (height-width-depth):

Standalone Power supply: 12 Vac/Vdc

IPK-437

Operating temperature: -10 to 60 °C

Up to 100 user codes

- Code length 4 to 6 digits.
- Electric lock release activation by Relay2 A (NA,NC). Programmable 1 to 99 sec. or bistable.
- Exit button input.
- Free access button (trades) input.
- Open Collector auxiliary output (150 mA max) to indicate sabotage attempt or door open/forced.



- Confirmation by keypad pulsation tone and acceptance or rejection of the code entered.
- Programming from the keypad by master code.
- Power supply 12 Vac / 12 Vdc
- Consumption: 6 mA (standby), 60 mA (active).
- Protection IPK 536

Weight: 0,700172 kg

Size of product when packed: 8,5x21x14,5 cm

EAN 13: 8424299036106
