

## DSM8WGF

8" Active Matrix Glass Fronted / Metal Case

### DSM8WGF

|                               |   |
|-------------------------------|---|
| Panel Type                    | 8" (4:3) LED Monitor With Glass Front   |
| Case Type                     | Metal                                   |
| Maximum Resolution            | 800 (H) x 600 (V)                       |
| Active Display Area           | 162.0 x 121.5 (V) m m                   |
| Pixel Pitch                   | 0.675 (H) x 0.2025 (V) mm               |
| Bezel Thickness               | 22mm                                    |
| Contrast Ratio                | 500 : 1 Ratio                           |
| Brightness                    | 250 cd/ m <sup>2</sup>                  |
| Response Time                 | 10ms - 15ms                             |
| Viewing Angle                 | U/D: 50° / 70°, L/R: 70° / 70°          |
| Display Colours               | 16.7 M                                  |
| Video Synchronization         | Yes                                     |
| PC Compatible Frequency       | 30-80KHz(H) / 50-75Hz(V) Max. 800 x 600 |
| Adjustable Colour Temperature | 9300K / 6500K / 5800K / User            |
| Video Compatibility           | Multi-Standard for NTSC / PAL           |
| Aspect Ratio                  | 4 : 3 Ratio                             |
| VGA Auto Frequency correction | Yes                                     |
| Number of Speakers            | No                                      |
| Sound Demodulation            | N/A                                     |
| Mute                          | N/A                                     |
| Work Humidity                 | 20 % - 70 %                             |
| Work Temperature              | -10 to 50 °C                            |
| Volume +/- Power On/Off       | Power ON/OFF Only                       |



### POWER

|                   |                        |
|-------------------|------------------------|
| Power Supply      | 12VDC, 1 amp           |
| Voltage           | AC100 - 240V 50 / 60Hz |
| Power Consumption | < 12W in "ON"          |

### IN/OUT INTERFACE

|                            |                                     |
|----------------------------|-------------------------------------|
| Video Interface            | VGA In BNC In x 2                   |
| Audio Interface            | None                                |
| Power Interface            | AC In x 1                           |
| Termination                | 75 Ohms (Automatic termination)     |
| Safety & EMC Certification | ROHS-2, CE, FCC, C-Tick, E13, WEEE  |
| Vesa Standard Mount        | 75 x 75 mm                          |
| Stand Type                 | Multi Functional Desktop/Wall mount |
| Colour                     | Black                               |
| Packing Dimension          | 283 (W) x 295 (H) x 105 (D) mm      |
| NET Weight                 | 1.4 Kgs                             |
| GROSS Weight               | 2.0 Kgs                             |

### OSD CONTROLS

Contrast, Brightness, Language, Colour, Rotation up/down & L/R, Input Source (VGA,AV1AV2), Reset

### OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

### ACCESSORIES

Power Supply, Remote Control, Multi Functional Bracket Desktop/Wall Mount, User Manual.



