



EasiKey 250 Controller

The Easikey 250 is a simple to use, standalone door controller. PAC's new and improved design allows access to one or two doors for up to 250 users, or 500 when paired with another PAC 250.

Compatible with the PAC GS3 LF reader range, the Easikey 250 is a cost effective solution suitable for compact applications such as tenanted buildings and small commercial offices, providing easy to manage access control system.

The programming features of the EasiKey 250 have been designed with the convenience of the system administrator in mind. Adding, deleting and editing users and keyholders is quick and simple with up to 3 Master Keys at hand.

The integral LCD display provides easy to understand instructions and the built-in GS3 administration reader makes the programming of users effortless. The Easikey 250 also offers language support of English, Dutch, German, Norwegian and Swedish.

The EasiKey 250 is the ideal controller for small applications where the simplicity and convenience of managing the system are a key element of ensuring security around the site on a day-to-day basis.

- "Out of the box" 1 or 2 door standalone access control solution
- Up to 250 key holders or 500 when paired
- Works with both PAC and KeyPAC technologies
- Displays last 5 users, detailing user ID and Door
- Compatible with OneproX™ GS3 LF Readers plus legacy PAC, KeyPAC and EasiKey readers
- Fail Safe or Fail Secure option with Lock Time Settings
- Buzzer/sounder options
- Battery back-up facility



Contact our dedicated customer services team on:

+44 (0) 161 406 3400

to find out how you can start benefiting from a tailored PAC security system that accommodates your business' requirements.

"When we decided to manage our own stock, controlling access was vital and the PAC 250 was the ideal choice. Simple to programme and easy to install, we quickly had both the area and our goods secure."

Part Numbers:

22370 - Unboxed EasiKey 250 Controller

22275 - Boxed EasiKey 250 (Pre-wired controller in metal case with no cut-out & 3Amp PSU)

22277 - Boxed EasiKey 250 (Pre-wired controller in a metal case with cut-out & 3Amp PSU)

Customer Support:

+44 (0) 161 406 3400

customerservices@stanleysecurityproducts.com

PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ

www.stanleysecurityproducts.com



EasiKey 250 Controller

SPECIFICATIONS

Model	EasiKey 250
Part Numbers	<ul style="list-style-type: none">22370 - Unboxed Easikey 250 Controller22275 - Boxed EasiKey 250 (Pre-wired controller in metal case with no cut-out & 3Amp PSU)22277 - Boxed EasiKey 250 (Pre-wired controller in a metal case with cut-out & 3Amp PSU)
Dimensions	<ul style="list-style-type: none">Un-Boxed – H90 x W198 x D28 (mm)Boxed with cut-out – H406 x W255 x D72 (mm)Boxed without cut-out – H420 x W350 x D100 (mm)
Temperature	Operating - Interior Equipment: 0° ++ 50°C
Humidity	Operating 0% to 90% relative humidity, non condensing
Supported Reader Protocol	PAC
Supported Credential Format	PAC, KeyPAC, STANLEY
Number of Doors	Two-Door Controller - One reader per channel
Reader Distance from Controller	100m per reader when using 0.22mm 8-core alarm cable
Controller Inputs	Request To Exit (RTE)
Controller Outputs	2 x 2Amp @ 24V DC
Additional Connections	None
Configuration	All configuration carried out locally using integral reader and buttons
Database	250 credentials configured numerically or 500 when used in parallel with another EasiKey 250
Event Storage	Last 5 events
External Configuration Options	None
Power Requirements	10.5V DC to 20V DC or 8V DC to 14.5V DC 50/60HZ @100mA
Warranty	5 years against electronic failure
Compliance	CE, RoHS & WEEE Compliant

EK250/10.15

Ordering Information:

+44 (0) 161 406 3400

customerservices@stanleysecurityproducts.com

PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ

www.stanleysecurityproducts.com